



THE ORIGINAL WHOLE-HOUSE AIR PURIFIER

APCO® cleans the air by combining UVC light and activated carbon; two technologies that are effective at neutralizing germs and odors by reducing chemical vapors known as volatile organic compounds (VOCs).

FEATURES/BENEFITS

Duct or magnet mount	Whole-house air purification
Easy to install	Neutralizes odors & VOCs
Lifetime carbon cells	Help reduce mold, bacteria, & viruses
Ozone-free	Improves indoor air quality
Lifetime warranty	Inhibits HVAC mold growth



Duct Mount in furnace



Duct Mount Dual in air handler





SAFELY AND EFFECTIVELY TREAT THE OTHER 2/3RDS

Conventional filters are only effective against particulates, like dust. APCO® safely reduces both biological and chemical contaminants inside the air system and throughout the building.

34%
BIOLOGICAL:
mold, bacteria and viruses
CHEMICAL:
odors and VOC chemical vapors found in the air

35%
PARTICULATES:
dust, pet dander, spores, dust mites

FILTERS ALONE

CLEANS THE COIL AND DRAIN PAN

Helps keep the HVAC system running efficiently and extend its life.






APCO Helps Neutralize Mold, Bacteria, Viruses, and Allergens






APCO CARBON

- High or low-voltage internal power supply
- · Slotted flanges enhance air flow
- · Ideal for HVAC systems from to 3-7 tons





18-32 VAC MODELS


TUV-APCO-ER TUV-APCO-ER2 TUV-APCO-DER TUV-APCO-DER2

120-277 VAC MODELS

TUV-APCO-SIP2 TUV-APCO-DIP2

APCO RT

- High or low-voltage remote power supply
- · Requires only 10" clearance within the duct



18-32 VAC RT MODELS


TUV-APCO-RT-ER2

120-277 VAC RT MODELS

TUV-APCO-RT-ST2 TUV-APCO-RT-DT2

APCO MAG

- · High or low-voltage remote power supply
- · Removable magnet for internal mounting
- · Ideal for package units



18-32 VAC MAG 15 MODELS TUV-APCO-MAG15-ER2

120-277 VAC MAG 15 MODELS TUV-APCO-MAG15-DT2

18-32 VAC MAG 11 MODELS TUV-APCO-MAG11-ER2





Original APCO Specs	
UV Lamp	254 nm UVC, quartz hot filament
Dimensions	Cell & Lamp: 5.8"W x 3.25"H x 13.2"D Enclosure: 7.6"L x 7.6"W x 2.2"D
ER models Electrical	18-32 VAC, 60 Hz, 0.68 Amps, 16 VA
SI DI models Electrical	120-277 VAC, 50/60 Hz, 0.41 amp/120V thru 0.18amp/277V
Pressure Drop	<0.01" w.c. @ 400 FPM
Warranty	Lifetime for all parts except lamp

Part Numbers				
18-32 VAC		Replacement Lamp		
TUV-APCO-ER TUV-APCO-ER2	1 Year Lamp 2 Year Lamp	TUVL-115 TUVL-215		
18-32 VAC with 2nd UV Lamp for Coils		Replacement Lamp		
TUV-APCO-DER TUV-APCO-DER2	1 Year Lamp (2) 2 Year Lamp (2)	TUVL-115, TUVL-115P TUVL-215, TUVL-115P		
120-277 VAC		Replacement Lamp		
TUV-APCO-SI2-P	2 Year Lamp	TUVL-215		
120-277 VAC with 2nd UV Lamp for Coils		Replacement Lamp		
TUV-APCO-DI2-P	2 Year Lamps (2)	TUVL-215, TUVL-215P		

APCO RT Specs				
UV Lamp	254 nm UVC, quartz hot filament			
Dimensions	Cell & Lamp: 2.5"W x 2.5"H x 9.4"D Enclosure: 4.83"L x 4.83"W x 2.29"D			
ER models Electrical		18-32 VAC, 60 Hz, 0.68 Amps, 16 VA		
ST DT models Electrical	120-277 VAC, 50/60 Hz, 0.41 amp/120V thru 0.18amp/277V			
Pressure Drop	<0.0	<0.01" w.c. @ 400 FPM		
Warranty	Life	Lifetime for all parts except lamp		
Part Numbers				
18-32 VAC		Replacement Lamp		
TUV-APCO-RT-E	R2	2 Year Lamp	TUVL-211	
18-32 VAC with 2nd UV Lamp for Coils Replacement Lamp		Replacement Lamp		
TUV-APCO-RT-ST2		2 Year Lamp (2)	TUVL-211	
120-277 VAC with 2nd UV Lamp for Coils Replacement Lamp				
TUV-APCO-RT-DT	2	2 Year Lamps (2)	TUVL-211, TUVL-215P	

Advano	n UVC, quartz hot fila ced Monolithic Adsor tary absorption med			
Advano	ced Monolithic Adsor tary absorption med			
roprie	tary absorption med	ptive PCO cell with		
	catalyst	Advanced Monolithic Adsorptive PCO cell with proprietary absorption media and proven TiO2 photo-catalyst		
<0.01" w.c. @ 400 FPM				
APCO MAG11 5.5"W x 4"H x 13"D APCO MAG15 5.5"W x 4"H x 17"D				
<0.01" w.c. @ 400 FPM				
18-32 VAC, 60 Hz, 0.68 Amps, 16 VA Low-voltage power-supply				
120-277 VAC, 50/60 Hz, 0.41 amp/120V thru 0.18amp/277V High-voltage power-supply				
Lifetime for all parts except lamp				
APCO Mag 11 Part Numbers				
18-32 VAC		Replacement Lamp		
TUV-APCO-MAG11-ER2 2 Year Lamp		TUVL-211P		
APCO Mag 15 Part Numbers				
18-32 VAC		Replacement Lamp		
TUV-APCO-MAG15-ER2 2 Year Lamp		TUVL-215P		
120-277 VAC		Replacement Lamp		
TUV-APCO-MAG15-DT2 2 Year Lamp (2)		TUVL-215P		
	APCO I APCO I 0.001" 8-32 \ .ow-vo 20-27 0.41 an digh-vo .ifetim t Nur ER2	APCO MAG11 5.5"W x 4"H x APCO MAG15 5.5"W x 4"		

APCO TECHNICAL DATA		
UV Lamp	254 nm UVC Spectrum Quartz Hot Filament	
Carbon Cell	Advanced Monolithic Adsorptive Carbon cell with proprietary ab- sorption j and proven TiO2 photo- catalyst	
Cell per In2	16	
Cell Surface Area	250 m2/gm	
Bulk Density	1.44 gm/cm2	
Pressure Drop	<0.01" w.c. @ 400 FPM	
VOC Activity	40-60% absorption per pass	
Max Operating Temp.	400 degrees F	









DESIGNED & ASSEMBLED IN THE U.S.A.





