



## COMMERCIAL POWER SUPPLY ELECTRICAL DATA:

For Fresh-Aire UV 18" - 24" - 32" - 46" - 60" High output Lamps

LAMPS	SYSTEM TYPE	POWER SUPPLY	LAMP WATTAGE	AMPERAGE @ 120V	AMPERAGE @ 277V
TUVCL-218-HO	SINGLE	TUVCPS-HS	48	0.31	0.14
TUVCL-218-HO	DUAL	TUVCPS-H32D	48 (x2)	0.70	0.30
TUVCL-224-HO	SINGLE	TUVCPS-HS	57	0.45	0.21
TUVCL-224-HO	DUAL	TUVCPS-H32D	57 (x2)	0.95	0.41
TUVCL-232-HO	SINGLE	TUVCPS-HS	80	0.67	0.29
TUVCL-232-HO	DUAL	TUVCPS-H32D	80 (x2)	1.33	0.58
TUVCL-246-HO	SINGLE	TUVCPS-HS	100	0.83	0.36
TUVCL-246-HO	DUAL	TUVCPS-H46-60D	100 (x2)	1.67	0.72
TUVCL-260-HO	SINGLE	TUVCPS-HS	130	1.32	0.57
TUVCL-260-HO	DUAL	TUVCPS-H46-60D	130 (x2)	2.6	1.4

All Fresh-Aire UV lamps are keyed at the base and use proprietary connectors between the lamp and ballast. Using any other lamp manufacturer will void the lifetime warranty on the power supply.

[www.FRESH-AIREUV.com](http://www.FRESH-AIREUV.com)